

## K 750 S | 7 kg class drilling and breaking hammer



- Large, heavy weight striker delivers maximum 11.9 J impact energy.
- Variolock (12 positions) for selecting the most appropriate chisel angle.
- 6 m cable.
- Powerful 1550 watt ensures maximum power yet due to better heat dissipation, guarantees maximum possible durability.
- Fullwave electronics for precise power adjustment to application.
- Soft start for precise start of drilling/chiselling.
- AVS (Anti-Vibration-System) and soft grip on front and back handle.

|                                                                  | K 750 S                            |
|------------------------------------------------------------------|------------------------------------|
| Blow energy (EPTA)(J)                                            | 11.9                               |
| Full load hammer action (bpm)                                    | 2740                               |
| Full load speed (soft hammer) (rpm)                              | 240                                |
| Max. drilling core bit (mm)                                      | 150                                |
| Max. drilling solid bit (mm)                                     | 50                                 |
| Max. drilling tunnel bit (mm)                                    | 80                                 |
| No load speed (rpm)                                              | 300                                |
| Power input (W)                                                  | 1550                               |
| Sound power level (dB(A))                                        | 107.4                              |
| Sound power level uncertainty (dB(A))                            | 3                                  |
| Sound pressure level (dB(A))                                     | 96.4                               |
| Sound pressure level uncertainty (dB(A))                         | 3                                  |
| Standard equipment                                               | Additional straight handle, grease |
| Supplied in                                                      | Kitbox                             |
| Vibration chiseling (m/s <sup>2</sup> )                          | 9.1                                |
| Vibration chiselling uncertainty (m/s <sup>2</sup> )             | 1.5                                |
| Vibration drilling (m/s <sup>2</sup> )                           | 9.5                                |
| Vibration drilling into concrete [m/s <sup>2</sup> ]             | 9.5                                |
| Vibration drilling into concrete uncertainty [m/s <sup>2</sup> ] | 1.5                                |
| Weight (kg)                                                      | 8.2                                |